

PROCESS WEIGHING Applications

- Inventory Measurement
- Level Measurement
- Batching/Blending
- Filling/Dispensing/
Dosing
- Check Weighing



Connect, view and control
one to four instruments
on one display panel



Features

THE HARDY PROCESS TOOLBOX

The Hardy Process Toolbox is a set of productivity tools that delivers value across process weighing functions. Each tool saves time, increases accuracy, improves efficiency or reduces risk in your process weighing applications.



Electronic calibration without test weights

C2[®] eCAL[™]

Weighing system monitoring, diagnostics and troubleshooting

**IT[®] INTEGRATED
TECHNICIAN**

Vibration immunity from mechanical noise

WAVERSAVER[®]

**Easy to configure and setup with
a Rockwell Automation PLC
Rockwell Add-on-Profile
HMI Faceplate/AOIs**

HI 6500 series are EtherNet/IP[®] enabled weight processors with a Rockwell Add-On-Profile and HMI Faceplates. They have a big, bright multi-channel display and deliver fast, high-resolution weight readings. They also feature alternative communication options. Weight processors are used as front ends to control systems or standalone for all types of general weighing applications. Operating blind or with a display, they measure, condition and communicate weight without any need to control.

SOLID PERFORMANCE

The HI 6500 series delivers stable processed weight with a resolution of 1:10:000, and an update speed of 110 updates per second (processor, display and comm.). They enhance the productivity of process manufacturing systems where fast, precise weight-based controls are critical. They offer you many communication choices including EtherNet/IP, Modbus TCP & RTU, and Analog 4-20mA.

INSTALLATION YOUR WAY

For panel mounting, simply drill five holes to mount the keypad/display on the front and the instrument to the back. For blind or remote mounting, just snap its built-in clip onto a DIN rail or mount on a wall. The HI 6500 series fits in a 2" deep cabinet!

EASY TO READ

For maximum visibility and usability, the HI 6500 series features a big, rugged high-contrast display with a 140 degree viewing angle for easy reading at a distance. Discrete status messaging makes it easy to use!

MULTI-CHANNEL DISPLAY

To save space and energy, the HI 6500 series can deliver the weight readings of up to four instruments on one big, bright display panel simultaneously! Name your display inputs for easy ID and rearrange them in any order.

LOW POWER CONSUMPTION

Each instrument consumes just 5 watts nominal and 7 watts max, saving energy costs while driving up to 8 load points. Share a keypad/display with four instruments and save 1.5 watts more per blind unit.

EASE OF SET-UP & CALIBRATION

A set-up wizard guides you through installation and calibration, or use the embedded web server to set up parameters from anywhere on your network. Front panel keys and menus enable quick, easy setup with help text. Use Hardy's exclusive C2[®] for automatic system calibration, which saves hours of start-up and maintenance time. A Rockwell Add-On-Profile makes PLC setup fast and easy, while HMI Faceplates/AOIs make it easy to use without programming.

INTEGRATED TECHNICIAN[®]

Quickly and easily troubleshoot the weighing system from the front panel of the display or connected control system using Hardy's proprietary IT built-in system diagnostics.

VIBRATION IMMUNITY

Hardy's WAVERSAVER[®] technology suppresses vibration and mechanical noise, dramatically reducing scale settling time and increasing the speed of stable gross and net weight readings.

COMPONENTS TO COMPLETE YOUR HARDY SYSTEM

Hardy Bench Scales, Floor Scales and Load Points

Hardy carries a wide variety of strain gauge load points and scale bases to accommodate your application requirements.



ADVANTAGE Series
Load Point with
C2 Calibration



Hardy Bench
Scales

Weighing Instruments Dedicated to Your Applications

Controllers, Weigh Modules,
Transmitters



Allen-Bradley® Compatible
Plug-in Weigh Scale Modules



HI 3000 & HI 4000
Controllers and
HI 6000 Series



SPECIFICATIONS

Performance:

Resolution

- Stable processed weight 1:10,000
- Maximum displayed resolution: 1:999,999
- Internal resolution 1:8,388,608

Update Rate

- Processed weight, display & communications: 110 times per second
- Unprocessed weight (A/D conversion): 4800 times per second

Modes:

- Gross, Net, Piece Count

Units of Measure:

- Ounce, Pound, Ton, Gram, Kg, Metric Ton, Pieces

Weight Processing

- WAVESEVER®: .25 Hz to 7.5 Hz
- Averaging: 1 to 255 User-selectable in single increments

Display:

- 80:1 contrast ratio with 4.3" effective viewing area
- 140° viewing angle

Multi-channel Display:

- Control configure, and view one to four instruments on a single front panel (up to 3 blind and one with a display)

Calibration Methods:

- C2® calibration without test weights
- Traditional calibration with test weights

Excitation:

- 5VDC

Number of Load Cells:

- Up to 8 at 350 Ω

Keypad:

- 5-Button Tactile

Mounting:

- DIN, low profile, panel, wall

Communications:

- EtherNet/IP (-EIP models)
- Ethernet UDP
- Ethernet TCP/IP (Embedded Webserver)
- Modbus RTU
- Modbus TCP (-EIP models)
- Analog 4-20mA (HI 6510 models)
- Profibus-DP (-PB models)

Communication Interface:

- Terminal, RJ-45
- USB setup and configuration saving

Power:

- 12-27 VDC
- 5 watts nominal with display
- 7 watts max with two IT junction boxes and 8 load points



All information within is subject to change without notice. Visit our website for latest specifications. WAVESEVER, C2, IT, ADVANTAGE and ANY-WEIGH are registered trademarks of Hardy Process Solutions, Inc. All other trademarks or registered trademarks are the property of their respective owners.

Temperature:

- -10°C to +60°C (14° F to 160°F)

Humidity:

- 0-90% non-condensing

Dimensions:

- 7" W x 3"H x 2 1/4" D (18 cm x 7.6 cm x 5.7 cm)

Certifications:

- Hazardous: Class I, II, III/Div2
- Safety: CE, UL & CUL
- EtherNet/IP ODVA Certification Level 3
- Profibus-DP DPV0

Warranty:

- Two-year warranty against defects in workmanship

MODEL NUMBERS

HI 6500 SERIES

HI6500-WP-00-EIP	EtherNet/IP configuration, no display
HI6500-WP-10-EIP	EtherNet/IP configuration, with display
HI6500-WP-00-PB	Profibus-DP configuration, no display
HI6500-WP-10-PB	Profibus-DP configuration, with display
HI6510-WP-00-EIP	Analog & EtherNet/IP, no display
HI6510-WP-10-EIP	Analog & EtherNet/IP, with display
HI6510-WP-00-PB	Analog and Profibus-DP, no display
HI6510-WP-10-PB	Analog and Profibus-DP, with display

Get more information about
the HI 6500 Series at

www.hardysolutions.com
hardyinfo@hardysolutions.com
or 1-800-821-5831

HARDY
PROCESS SOLUTIONS
Measurement • Automation • Productivity

9440 Carroll Park Dr.
San Diego, CA 92121
tel. +1-858-278-2900
tel. 800-821-5831
fax +1-858-278-6700
www.hardysolutions.com
hardyinfo@hardysolutions.com



HI 6500 Series 0718
0400-6500D

www.hardysolutions.com • 800.821.5831